Atty. Dkt. PC-1228

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Non to

Claim 1(Currently Amended). A seal tight device, comprising:

a first rigid sleeve;

a second rigid sleeve; and

a resilient member having a first portion which separates an end of the first sleeve from an end of the second sleeve, and having a second portion substantially perpendicular to the first portion which is exterior to the first sleeve and the second sleeve, and having a third portion extending outward from the second portion, the third portion having at least one raised ridge on a surface portion of the third portion, wherein the first sleeve, the second sleeve and the resilient member pass through a boundary that separates two spaces from one another, the resilient member being located inside the boundary.

Claim 2(Original). The seal tight device of claim 1, wherein the first sleeve and the second sleeve are each PVC sleeves.

Claim 3(Original). The seal tight device of claim 1, wherein the resilient member includes: a rubber sleeve.

Claim 4(Canceled).

Claim 5(Canceled).

Claim (Currently Amended). The seal tight device of claim 51, wherein the third portion includes:

Atty. Dkt. PC-1228

a washer configuration.

Claim (Currently Amended). The seal tight device of claim §1, wherein the first portion, the second portion and the third portion includes: a substantially t cross-sectional shape.

Claim 8(Canceled).

Claim (Original). The seal tight device of claim 1, wherein the boundary is a wall.

Claim (Original). The seal tight device of claim 1, wherein the boundary is a floor.

Claim Li(Original). The seal tight device of claim 1, wherein the boundary includes: concrete.

Claim 12 (Original). The seal tight device of claim 1, further comprising: a fire stop adjacent to the second sleeve.

Claim 3(Original). The scal tight device of claim 1, further comprising:

a plumbing pipe inserted through the first sleeve, the resilient member and the second sleeve, wherein the resilient member forms a seal about the pipe which is substantially maintained during expansion and contraction of the seal tight device during heating and cooling conditions.

Claim 4(Previously Presented). The seal tight device of claim 1, further comprising: a conduit inserted through the first sleeve, the resilient member and the second sleeve, the pipe allowing electrical lines to pass therethrough, wherein the resilient

Atty. Dkt. PC-1228

member forms a seal about the conduit which is substantially maintained during expansion and contraction of the seal tight device during heating and cooling conditions.

Claim 15 (Currently Amended). A seal tight device system for walls and floors, comprising in combination:

a first rigid sloove extending through one side of a boundary, the boundary being selected from at least one of a wall, and a floor;

a second \underline{rigid} sleeve extending through a second side of the boundary opposite the first side;

a resilient member located in-side the boundary having a first portion which separates and end of the first sleeve from and end of the second sleeve , the resilient member having an inwardly protruding portion being the first portion, a second portion substantially adjacent to the first portion and positioned exterior to the first sleeve and the second sleeve, and a third portion extending away from and being substantially perpendicular to the second portion, the first and the second and the third portions forming a substantially t cross-sectional shape, the first sleeve, the second sleeve and the resilient member form a through-hole opening through and inside of the boundary; and

a pipe passing through the through-hole in the boundary, the pipe being selected from at least one of a plumbing pipe and an electrical conduit.

Claim 16(Canceled).

Claim 17 (Original). The seal tight device system of claim 18, further comprising: a fire stop adjacent to the second sleeve.

Claims 18-25(Canceled).

Claim 26(Canceled).

Atty, Dkt. PC-1228

Claim 27(Canceled).

Claim 28(New). A seal tight device, comprising:

a first sleeve;

a second sleeve; and

a resilient member having a first portion which separates the first sleeve from the second sleeve, wherein the first sleeve, the second sleeve and the resilient member pass through a boundary that separates two spaces from one another, the resilient member being located inside the boundary; and

a fire stop adjacent to the second sleeve.

Claim 29(New). A seal tight device, comprising:

a first sleeve;

a second sleeve; and

a resilient member having a first portion which separates the first sleeve from the second sleeve, wherein the first sleeve, the second sleeve and the resilient member pass through a boundary that separates two spaces from one another, the resilient member being located inside the boundary, the resilient member further includes a second portion substantially perpendicular to the first portion, which is exterior to the first sleeve and the second sleeve, the resilient member further includes a third portion extending outward from the second portion, wherein the third portion includes a raised ridge on a surface portion of the third portion.